

Taper- Kettenräder für Ketten nach DIN-Nr. 8187

Zähne- zahl z	Abmessungen in mm allgemein de dp		Artikel-Nr. Ketten Fuchs											
			321-400- (+Zähnezahl)				322-400- (+Zähnezahl)				323-400- (+Zähnezahl)			
			einfach		Buchse		zweifach		Buchse		dreifach		Buchse	
			dm	A		Typ	dm	A		Typ	dm	A		Typ
013 TL	87,5	79,59	63,0	25,0	1210	1								
014 TL	93,6	85,61	71,0	25,0	1610	1		30,3	1610	3				
015 TL	99,8	91,63	71,0	25,0	1610	1		30,3	1610	3	49,8	1615	5	
016 TL	105,5	97,65	75,0	25,0	1610	1		30,3	1610	3				
017 TL	111,5	103,67	76,0	25,0	1610	1		30,3	1610	3	49,8	2012	5	
018 TL	118,0	109,71	90,0	32,0	2012	1	89,0	32,0	2012	2				
019 TL	124,2	115,75	90,0	32,0	2012	1	95,0	32,0	2012	2	49,8	2012	5	
020 TL	129,7	121,78	90,0	32,0	2012	1	108,0	45,0	2517	2				
021 TL	136,0	127,82	102,0	45,0	2517	1	108,0	45,0	2517	2	49,8	2517	5	
022 TL	141,8	133,86	102,0	45,0	2517	1	108,0	45,0	2517	2				
023 TL	149,9	139,90	108,0	45,0	2517	1	108,0	45,0	2517	2	49,8	2517	5	
024 TL	153,9	145,94	108,0	45,0	2517	1	108,0	45,0	2517	2				
025 TL	160,0	152,00	108,0	45,0	2517	1	108,0	45,0	2517	2	49,8	2517	5	
026 TL	165,9	158,04	108,0	45,0	2517	1	108,0	45,0	2517	2				
027 TL	172,3	164,09	108,0	45,0	2517	1	108,0	45,0	2517	2	140,0	51,0	3020	4
028 TL	178,0	170,13	108,0	45,0	2517	1	108,0	45,0	2517	2				
030 TL	190,5	182,25	108,0	45,0	2517	1	108,0	45,0	2517	2	140,0	51,0	3020	4
038 TL	239,0	230,69	124,0	45,0	2517	1	152,0	51,0	3020	2	140,0	51,0	3020	4
045 TL	282,5	273,10	124,0	45,0	2517	1	154,0	51,0	3020	7	140,0	51,0	3020	4
057 TL	355,4	345,81	124,0	45,0	2517	6	160,0	51,0	3020	7	160,0	51,0	3020	8
076 TL	469,9	460,99	124,0	45,0	2517	6	160,0	51,0	3020	7	160,0	51,0	3020	8
095 TL	585,1	576,17	124,0	45,0	2517	6	160,0	51,0	3020	7	165,0	76,0	3030	8

3/4" x 7/16"
19,05 x 11,68 mm
12B - 1 - 2 - 3

Zähne- zahl z	Abmessungen in mm allgemein de dp		Artikel-Nr. Ketten Fuchs											
			321-510- (+Zähnezahl)				322-510- (+Zähnezahl)				323-510- (+Zähnezahl)			
			einfach		Buchse		zweifach		Buchse		dreifach		Buchse	
			dm	A		Typ	dm	A		Typ	dm	A		Typ
013 TL	117,0	106,12	78,0	25,0	1610	1								
014 TL	125,0	114,15	78,0	25,0	1610	1								
015 TL	133,0	122,17	78,0	25,0	1610	1		47,7	2012	3				
016 TL	141,0	130,20	90,0	32,0	2012	1		47,7	2517	3				
017 TL	149,0	138,22	90,0	32,0	2012	1		47,7	2517	3	79,6	2517	5	
018 TL	157,0	146,28	108,0	45,0	2517	1		47,7	2517	3				
019 TL	165,2	154,33	108,0	45,0	2517	1		47,7	2517	3	79,6	3020	5	
020 TL	173,0	162,38	108,0	45,0	2517	1		47,7	2517	3				
021 TL	181,2	170,43	108,0	45,0	2517	1	143,0	51,0	3020	2	79,6	3020	5	
022 TL	189,3	178,48	108,0	45,0	2517	1	150,0	51,0	3020	2				
023 TL	197,5	186,53	108,0	45,0	2517	1	160,0	51,0	3020	2	79,6	3525	5	
024 TL	205,5	194,59	108,0	45,0	2517	1	166,0	51,0	3020	2				
025 TL	213,5	202,66	108,0	45,0	2517	1	175,0	51,0	3020	2	79,6	3525	5	
026 TL	221,6	210,72	108,0	45,0	2517	1	175,0	51,0	3020	2				
027 TL	229,6	218,79	108,0	45,0	2517	1	175,0	51,0	3020	2	79,6	3525	5	
028 TL	237,7	226,85	108,0	45,0	2517	1	175,0	51,0	3020	2				
030 TL	254,0	243,00	160,0	51,0	3020	1	175,0	51,0	3020	2	79,6	3525	5	
038 TL	320,7	307,59	160,0	51,0	3020	1	160,0	76,0	3030	7	178,0	89,0	3535	8
045 TL	377,1	364,13	160,0	51,0	3020	1	160,0	76,0	3535	7	216,0	102,0	4040	8
057 TL	474,0	461,07	160,0	51,0	3020	6	175,0	89,0	3535	7	216,0	102,0	4040	8
076 TL	627,0	614,65	160,0	51,0	3020	6	175,0	89,0	3525	7	216,0	102,0	4040	8
095 TL	781,1	768,22	160,0	51,0	3020	6	216,0	102,0	4040	7	240,0	102,0	4040	8
114 TL	934,3	921,81	150,0	76,0	3030	6	216,0	102,0	4040	7	260,0	115,0	4545	8

1" x 17,02 mm
25,4 x 17,02 mm
16B - 1 - 2 - 3

Zähne- zahl z	Abmessungen in mm allgemein de dp		Artikel-Nr. Ketten Fuchs											
			321-600- (+Zähnezahl)				322-600- (+Zähnezahl)				323-600- (+Zähnezahl)			
			einfach		Buchse		zweifach		Buchse		dreifach		Buchse	
			dm	A		Typ	dm	A		Typ	dm	A		Typ
015 TL	167,9	152,72	108,0	45,0	2517	1								
017 TL	187,9	172,78	108,0	45,0	2517	1								
019 TL	208,1	192,91	108,0	45,0	2517	1								
021 TL	228,2	213,03	108,0	45,0	2517	1								
023 TL	248,3	233,17	108,0	45,0	2517	1								
025 TL	268,5	253,33	108,0	45,0	2517	1								
030 TL	318,9	303,75	160,0	51,0	3020	1								
038 TL	399,6	384,49	160,0	51,0	3020	6								

1 1/4" x 3/4"
31,75 x 19,05 mm
20B - 1