

Abmessungen / Technische Daten

Artikel-Nr. Ketten Fuchs	Größe Mt x A	Über- tragungs- werte	Anzahl Teller- feder	Abmessungen in mm			Bohrung		Antriebs- teilstärke F max. in mm	Abmessungen in mm			Gewicht m kg	Massen- trägheits- moment J kg cm³
				A	B (k7)	C	D vor- gebohrt	D max (H7)		G	H	L		
		Drehmoment Mt max. Nm							Buchsen- länge in mm					
T 190/95	190 x 95	190,0	1	95,0	60,0	66,0	15,0	30,0	10,5 16,0	4,0	52,0	17,0	1,840	15,83
T 340/95	340 x 95	340,0	2	95,0	60,0	66,0	15,0	30,0	10,5 16,0	4,0	52,0	17,0	1,840	15,83
T 350/120	350 x 120	350,0	1	120,0	73,0	77,0	20,0	45,0	16,0 21,0	4,0	64,0	21,0	3,330	43,01
T 650/120	650 x 120	650,0	2	120,0	73,0	77,0	20,0	45,0	16,0 21,0	4,0	64,0	21,0	3,330	43,01
T 650/140	650 x 140	650,0	1	140,0	90,0	86,0	20,0	60,0	16,0 22,0	4,0	85,0	23,0	5,600	98,10
T 1200/140	1200 x 140	1200,0	2	140,0	90,0	86,0	20,0	60,0	16,0 22,0	4,0	85,0	23,0	5,600	98,10
T 1000/170	1000 x 170	1000,0	1	170,0	100,0	93,0	28,0	65,0	18,0 24,0	4,6	90,0	26,5	8,400	231,30
T 1800/170	1800 x 170	1800,0	2	170,0	100,0	93,0	28,0	65,0	18,0 24,0	4,6	90,0	26,5	8,400	231,30
T 2200/200	2200 x 200	2200,0	1	200,0	120,0	105,0	35,0	80,0	17,0 24,0	5,0	110,0	27,0	12,000	385,00
T 4000/200	4000 x 200	4000,0	2	200,0	120,0	105,0	35,0	80,0	17,0 24,0	5,0	110,0	27,0	12,000	385,00
T 3800/254	3800 x 254	3800,0	1	254,0	140,0	120,0	48,0	90,0	25,0 32,0	5,0	125,0	33,0	21,000	1581,00
T 6800/254	6800 x 254	6800,0	2	254,0	140,0	120,0	48,0	90,0	25,0 32,0	5,0	125,0	33,0	21,000	1581,00
T 5500/280	5500 x 280	5500,0	1	280,0	170,0	120,0	48,0	120,0	25,0 32,0	5,0	155,0	33,0	26,000	1698,00