








HTD-Zahnriemenscheiben für Taper-Spannbuchsen



5M (Teilung = 5 mm) – für Zahnriemenbreite = 15 mm

Artikel-Nr. Ketten Fuchs	Zähne- zahl	Typ	Werk- stoff	Buchse				Abmessungen in mm					
					de	dp	dm	Di	df	W	E	L	
TL34-5M-15	34	3F	St	1108	52,97	54,11	–	–	57,0	22,0	–	–	
TL36-5M-15	36	3F	St	1108	56,15	57,30	–	–	60,0	22,0	–	–	
TL38-5M-15	38	3F	St	1108	59,34	60,48	–	–	66,5	22,0	–	–	
TL40-5M-15	40	3F	St	1108	62,52	63,66	–	–	71,0	22,0	–	–	
TL44-5M-15	44	3F	St	1108	68,89	70,03	–	–	75,0	22,0	–	–	
TL48-5M-15	48	8F	St	1210	75,25	76,39	59,0	–	83,0	22,0	3,0	25,0	
TL56-5M-15	56	8F	St	1210	87,39	89,13	70,0	–	93,0	22,0	3,0	25,0	
TL64-5M-15	64	8F	St	1210	100,72	101,86	80,0	–	106,0	22,0	3,0	25,0	
TL72-5M-15	72	8F	St	1610	113,45	114,59	92,0	–	120,0	22,0	3,0	25,0	
TL80-5M-15	80	8F	St	1610	126,18	127,32	92,0	–	135,0	22,0	3,0	25,0	
TL90-5M-15	90	8F	St	1610	142,10	143,24	92,0	–	150,0	22,0	3,0	25,0	
TL112-5M-15	112	8F	St	2012	177,11	178,25	110,0	–	184,0	20,0	12,0	32,0	
TL136-5M-15	136	7A	St	2012	215,31	216,45	110,0	199,0	–	20,0	6,0	32,0	



8M (Teilung = 8 mm) – für Zahnriemenbreite = 20 mm

Artikel-Nr. Ketten Fuchs	Zähne- zahl	Typ	Werk- stoff	Buchse				Abmessungen in mm					
					de	dp	dm	Di	df	W	E	L	
TL22-8M-20	22	5F	St	1108	54,65	56,02	–	37,0	60,0	28,0	6,0	22,0	
TL24-8M-20	24	5F	St	1108	59,75	61,12	–	44,0	66,0	28,0	6,0	22,0	
TL26-8M-20	26	5F	St	1108	64,85	66,21	–	45,0	70,0	28,0	6,0	22,0	
TL28-8M-20	28	5F	St	1108	70,08	71,30	–	50,0	75,0	28,0	6,0	22,0	
TL30-8M-20	30	5F	St	1108	75,13	76,39	–	58,0	82,5	28,0	6,0	22,0	
TL32-8M-20	32	5F	St	1610	80,16	81,49	–	63,0	87,0	28,0	3,0	25,0	
TL34-8M-20	34	5F	St	1610	85,22	86,58	–	64,0	91,0	28,0	3,0	25,0	
TL36-8M-20	36	5F	St	1610	90,30	91,67	–	68,0	97,0	28,0	3,0	25,0	
TL38-8M-20	38	5F	St	1610	95,39	96,77	–	72,0	102,0	28,0	3,0	25,0	
TL40-8M-20	40	5F	St	1610	100,49	101,86	–	76,0	106,0	28,0	3,0	25,0	
TL44-8M-20	44	8F	St	2012	110,67	112,05	92,0	–	120,0	28,0	4,0	32,0	
TL48-8M-20	48	8F	St	2012	120,86	122,23	96,0	–	128,0	28,0	4,0	32,0	
TL56-8M-20	56	8F	St	2012	141,23	142,60	110,0	–	150,0	28,0	4,0	32,0	
TL64-8M-20	64	8WF	St	2012	161,60	162,97	110,0	137,0	168,0	28,0	4,0	32,0	
TL72-8M-20	72	8WF	St	2012	181,97	183,35	110,0	158,0	192,0	28,0	4,0	32,0	
TL80-8M-20	80	8W	GG	2012	202,35	203,72	110,0	180,0	–	28,0	4,0	32,0	
TL90-8M-20	90	8W	GG	2012	227,81	229,18	110,0	204,0	–	28,0	4,0	32,0	
TL112-8M-20	112	8W	GG	2517	283,83	285,21	125,0	254,0	–	28,0	17,0	45,0	
TL144-8M-20	144	7A	GG	2517	365,32	366,69	125,0	336,0	–	28,0	12,0	45,0	

8M (Teilung = 8 mm) – für Zahnriemenbreite = 30 mm

Artikel-Nr. Ketten Fuchs	Zähne- zahl	Typ	Werk- stoff	Buchse				Abmessungen in mm					
					de	dp	dm	Di	df	W	E	L	
TL22-8M-30	22	5F	St	1108	54,65	56,02	–	37,0	60,0	38,0	16,0	22,0	
TL24-8M-30	24	5F	St	1108	59,75	61,12	–	44,0	66,0	38,0	16,0	22,0	
TL26-8M-30	26	5F	St	1108	64,85	66,21	–	44,0	70,0	38,0	16,0	22,0	
TL28-8M-30	28	5F	St	1210	70,08	71,30	–	50,0	75,0	38,0	13,0	25,0	
TL30-8M-30	30	3F	St	1615	75,13	76,39	–	–	82,5	38,0	–	38,0	
TL32-8M-30	32	3F	St	1615	80,16	81,49	–	–	87,0	38,0	–	38,0	
TL34-8M-30	34	3F	St	1615	85,22	86,58	–	–	91,0	38,0	–	38,0	
TL36-8M-30	36	3F	St	1615	90,30	91,67	–	–	97,0	38,0	–	38,0	
TL38-8M-30	38	3F	St	1615	95,39	96,77	–	–	102,0	38,0	–	38,0	
TL40-8M-30	40	3F	St	1615	100,49	101,86	–	–	106,0	38,0	–	38,0	
TL44-8M-30	44	5F	St	2012	110,67	112,05	–	86,0	120,0	38,0	6,0	32,0	
TL48-8M-30	48	5F	St	2012	120,86	122,23	–	90,0	128,0	38,0	6,0	32,0	
TL56-8M-30	56	5F	St	2012	141,23	142,60	–	110,0	150,0	38,0	6,0	32,0	
TL64-8M-30	64	8F	St	2517	161,60	162,97	125,0	–	168,0	38,0	7,0	45,0	
TL72-8M-30	72	8WF	St	2517	181,97	183,35	125,0	158,0	192,0	38,0	7,0	45,0	
TL80-8M-30	80	8W	GG	2517	202,35	203,72	125,0	180,0	–	38,0	7,0	45,0	
TL90-8M-30	90	8W	GG	2517	227,81	229,18	125,0	204,0	–	38,0	7,0	45,0	
TL112-8M-30	112	8W	GG	2517	283,83	285,21	125,0	254,0	–	38,0	7,0	45,0	
TL144-8M-30	144	8A	GG	2517	365,32	366,69	125,0	336,0	–	38,0	7,0	45,0	

Bestellbeispiel
 Zähnezahl 48
 Riementeilung 14 mm
 Riemenbreite 25 mm
 TL48 14 M 25