








HTD-Zahnriemenscheiben für Taper-Spannbuchsen



14M (Teilung = 14 mm) – für Zahnriemenbreite = 170 mm

Artikel-Nr. Ketten Fuchs	Zähne- zahl	Typ	Werk- stoff	Buchse				Abmessungen in mm				
					de	dp	dm	Di	df	W	E	L
TL38-14M-170	38	4F	St	3030	166,60	169,34	–	130,0	183,0	187,0	55,5	76,0
TL40-14M-170	40	4F	St	3030	175,49	178,25	–	138,0	188,0	187,0	55,5	76,0
TL44-14M-170	44	4F	St	3535	193,28	196,08	–	155,0	211,0	187,0	49,0	89,0
TL48-14M-170	48	4F	St	3535	211,11	213,90	–	175,0	226,0	187,0	49,0	89,0
TL56-14M-170	56	4F	GG	3535	246,76	249,55	–	210,0	256,0	187,0	49,0	89,0
TL64-14M-170	64	4F	GG	4040	282,41	285,21	–	240,0	296,0	187,0	42,5	102,0
TL72-14M-170	72	9W	GG	4040	318,06	320,86	230,0	280,0	–	187,0	42,5	102,0
TL80-14M-170	80	9W	GG	4040	353,71	356,51	230,0	315,0	–	187,0	42,5	102,0
TL90-14M-170	90	9A	GG	4040	398,28	401,07	230,0	360,0	–	187,0	42,5	102,0
TL112-14M-170	112	9A	GG	5050	496,32	499,11	265,0	457,0	–	187,0	30,0	127,0
TL144-14M-170	144	9A	GG	5050	638,92	641,71	265,0	600,0	–	187,0	30,0	127,0
TL168-14M-170	168	9A	GG	5050	745,87	748,66	265,0	706,0	–	187,0	30,0	127,0
TL192-14M-170	192	9A	GG	5050	852,82	855,62	265,0	813,0	–	187,0	30,0	127,0
TL216-14M-170	216	9A	GG	5050	959,76	962,57	265,0	920,0	–	187,0	30,0	127,0



Bestellbeispiel

			Zähnezahl 48
			Riementeilung 14 mm
TL48	14 M	170	Riemenbreite 170 mm