




Ketten- führungen



Typ GR 1 für Einfach- Ketten

Artikel-Nr. Ketten Fuchs	Bezeichnung DIN-Nr. 8187	p × b1	b	B	h	H
GR1-04-1	04-1	6,0 × 2,8 mm	2,6	10,0	1,0	10,0
GR1-05B-1	05 B-1	8,0 × 3,0 mm	2,8	10,0	1,5	10,0
GR1-053-1	053-1	3/8 × 5/32"	3,8	15,0	1,5	10,0
GR1-06B-1	06 B-1	3/8 × 7/32"	5,5	15,0	1,5	10,0
GR1-081-1	081-1	1/2" × 3,3 mm	3,0	12,0	1,5	10,0
GR1-083-1	083-1	1/2 × 3/16"	4,7	15,0	1,6	10,0
GR1-084-1	084-1	1/2 × 3/16"	4,6	17,0	2,0	10,0
GR1-085-1	085-1	1/2 × 1/4"	6,2	20,0	2,1	10,0
GR1-08B-1	08 B-1	1/2 × 5/16"	7,5	20,0	2,2	10,0
GR1-086-1	086-1	5/8 × 1/4"	6,3	20,0	2,6	10,0
GR1-10B-1	10 B-1	5/8 × 3/8"	9,3	20,0	2,6	15,0
GR1-12B-1	12 B-1	3/4 × 7/16"	11,2	25,0	3,0	15,0
GR1-16B-1	16 B-1	1" × 17,02 mm	16,5	40,0	3,5	15,0
GR1-20B-1	20 B-1	1 1/4 × 3/4"	19,0	45,0	4,2	15,0
GR1-24B-1	24 B-1	1 1/2 × 1"	24,7	60,0	5,5	15,0
GR1-28B-1	28 B-1	1 3/4 × 1 1/4"	30,1	75,0	6,8	20,0
GR1-32B-1	32 B-1	2" × 1 1/4"	30,1	80,0	7,7	20,0

Typ GR 2 für Zwei- fach-Ketten

Artikel-Nr. Ketten Fuchs	Bezeichnung DIN-Nr. 8187	p × b1	a	b	B	h	H
GR2-05B-2	05 B-2	8,0 × 3,0 mm	3,1	2,8	16,0	1,5	10,0
GR2-06B-2	06 B-2	3/8 × 7/32"	5,1	5,5	25,0	1,5	10,0
GR2-08B-2	08 B-2	1/2 × 5/16"	6,5	7,5	35,0	2,2	10,0
GR2-10B-2	10 B-2	5/8 × 3/8"	7,4	9,3	40,0	2,6	10,0
GR2-12B-2	12 B-2	3/4 × 7/16"	8,4	11,2	45,0	3,0	10,0
GR2-16B-2	16 B-2	1" × 17,02 mm	15,4	16,5	48,0	3,5	15,0
GR2-20B-2	20 B-2	1 1/4 × 3/4"	17,4	19,0	55,0	4,2	15,0
GR2-24B-2	24 B-2	1 1/2 × 1"	23,4	24,7	72,0	5,5	20,0
GR2-28B-2	28 B-2	1 3/4 × 1 1/4"	29,1	30,1	89,0	6,8	25,0
GR2-32B-2	32 B-2	2" × 1 1/4"	28,1	30,1	88,0	7,7	30,0

Typ GR 3 für Dreifach- Ketten

Artikel-Nr. Ketten Fuchs	Bezeichnung DIN-Nr. 8187	p × b1	a	b	B	h	H	e
GR3-06B-3	06 B-3	3/8 × 7/32"	5,1	5,5	35,0	1,5	10,0	4,2
GR3-08B-3	08 B-3	1/2 × 5/16"	6,5	7,4	44,0	2,2	10,0	4,4
GR3-10B-3	10 B-3	5/8 × 3/8"	7,4	9,2	53,0	2,6	10,0	5,3
GR3-12B-3	12 B-3	3/4 × 7/16"	8,4	11,2	62,0	3,0	10,0	5,9
GR3-16B-3	16 B-3	1" × 17,02 mm	15,4	16,5	104,0	3,5	15,0	11,9

Standardlänge: 2000 mm. Auf Wunsch jede Stärke und Länge lieferbar.
Weitere Kettenführungen, sowie Riemenführungen auf Anfrage.