




ROSTA-Spannelemente




Support Typ WS




Artikel-Nr. Ketten Fuchs	Typ	passend zu SE	Abmessungen in mm															Gewicht kg
			A	B	C	D	E	F	G	H	J	K	L	M	N	O		
06 590 001	WS 11	11	6,5	5,5	7,0	7,5	30,0	13,0	11,5	27,0	4,0	45,0	30,0	46,0	35,0	10,0	0,08	
06 590 002	WS 15	15	8,5	6,5	7,0	7,5	40,0	13,0	13,5	34,0	5,0	55,0	32,0	58,0	44,0	12,0	0,15	
06 590 003	WS 18	18	10,5	8,5	9,5	10,0	50,0	15,5	16,5	43,0	6,0	70,0	38,0	74,0	55,0	20,0	0,28	
06 590 004	WS 27	27	12,5	10,5	11,5	12,5	65,0	21,5	21,0	57,0	8,0	90,0	52,0	98,0	75,0	25,0	0,70	
06 590 005	WS 38	38	16,5	12,5	14,0	15,5	80,0	24,0	21,0	66,0	8,0	110,0	55,0	116,0	85,0	35,0	0,90	
06 590 006	WS 45	45	20,5	12,5	18,0	20,0	100,0	30,0	26,0	80,0	10,0	140,0	66,0	140,0	110,0	40,0	1,80	

Spannrad Typ N



Artikel-Nr. Ketten Fuchs	Typ	Für Rollenketten DIN-Nr. 8187	Zähne- zahl	Abmessungen in mm				Gewicht in kg
				A	B	C	D	
06 500 001	P3/8"-10	ISO 06 B	15	10,0	5,3	9,0	45,81	0,06
06 500 002	P1/2"-10	ISO 08 B	15	10,0	7,2	9,0	61,08	0,15
06 500 003	P1/2"-12	ISO 08 B	15	12,0	7,2	12,0	61,08	0,15
06 500 004	P5/8"-12	ISO 10 B	15	12,0	9,1	12,0	76,36	0,27
06 500 005	P5/8"-20	ISO 10 B	15	20,0	9,1	15,0	76,36	0,29
06 500 006	P3/4"-12	ISO 12 B	15	12,0	11,1	12,0	91,63	0,47
06 500 007	P3/4"-20	ISO 12 B	15	20,0	11,1	15,0	91,63	0,47
06 500 008	P1"-20	ISO 16 B	13	20,0	16,1	15,0	106,14	0,88
06 500 009	N1 1/4"-20	ISO 20 B	13	20,0	18,5	15,0	132,67	1,60
06 500 010	N1 1/2"-20	ISO 24 B	11	20,0	24,1	15,0	135,23	1,93

Kettengleiter Typ P



Artikel-Nr. Ketten Fuchs	Typ	Für Rollenketten DIN-Nr. 8187	Abmessungen in mm				Gewicht in kg
			A	B	C	D	
06 540 001	P3/8"	06 B	8,0	10,2	37,0	74,0	0,02
06 540 002	P1/2"	08 B	10,0	13,9	48,0	96,0	0,03
06 540 003	P5/8"	10 B	10,0	16,6	63,0	126,0	0,05
06 540 004	P3/4"	12 B	12,0	19,5	72,0	148,0	0,07